

High modulus polyester monofilament mesh
for technical screen printing applications



Thread type

L : Conjugated Polyester Monofilament (27µmφ - 30 µmφ)
UX: Super High Modulus Polyester Monofilament (33µmφ - 45 µmφ)
EX: High Modulus Polyester Monofilament

NBC Meshtec inc.

Category	Mesh code					Mesh Count		Weaving	Thread diameter µm	Mesh thickness		Mesh opening µm	Open Area %	Theoretical ink volume	
	Thread type	Mesh/cm	Thread dia. mm	Mesh/inch	Weaving	Tolerance ±3%				115-155cm µm	165cm & wider µm			115-155cm cm ³ /m ²	165cm & wider cm ³ /m ²
						/cm	/inch								
α_series	L-	200	-024/	508	PW	200	508	1:1 PW	24	36 ±2µm	N/A	24	23	8.3	N/A
α_series	L-	200	-027/	508	TW	200	508	2:2 TW	27	50 ±3µm	N/A	22	19	9.7	N/A
α_series	L-	180	-027/	460	PW	180	460	1:1 PW	27	41 ±2µm	42 ±3µm	24	19	7.7	7.9
α_series	L-	180	-030/	460	TW	180	460	2:2 TW	30	55 ±3µm	56 ±4µm	23	17	9.5	N/A
α_series	L-	165	-027/	420	PW	165	420	1:1 PW	27	40 ±2µm	41 ±3µm	30	25	9.8	10.1
α_series	L-	165	-030/	420	PW	165	420	1:1 PW	30	45 ±2µm	46 ±3µm	25	18	8.0	8.2
α_series	UX	165	-033/	420	TW	165	420	2:2 TW	33	60 ±3µm	60 ±3µm	24	16	9.4	9.4
α_series	L-	150	-027/	380	PW	150	380	1:1 PW	27	40 ±2µm	41 ±3µm	38	32	12.9	13.3
α_series	L-	150	-030/	380	PW	150	380	1:1 PW	30	45 ±2µm	46 ±3µm	33	24	11.0	11.2
α_series	UX	150	-033/	380	PW	150	380	1:1 PW	33	48 ±2µm	49 ±3µm	27	16	7.8	8.0
α_series	UX	150	-035/	380	TW	150	380	2:2 TW	35	64 ±3µm	64 ±3µm	30	20	12.9	12.9
α_series	L-	140	-027/	355	PW	140	355	1:1 PW	27	40 ±2µm	41 ±3µm	44	38	15.1	15.5
α_series	L-	140	-030/	355	PW	140	355	1:1 PW	30	45 ±2µm	46 ±3µm	39	30	13.4	13.7
α_series	UX	140	-035/	355	PW	140	355	1:1 PW	35	53 ±2µm	54 ±3µm	32	19	10.3	10.5
α_series	UX	140	-035/	355	TW	140	355	2:1 TW	35	61 ±3µm	61 ±3µm	34	23	13.8	13.8
α_series	L-	130	-027/	330	PW	131	334	1:1 PW	27	40 ±2µm	41 ±3µm	49	42	16.6	17.0
α_series	L-	130	-030/	330	PW	131	334	1:1 PW	30	45 ±2µm	46 ±3µm	44	33	15.1	15.4
α_series	UX	130	-035/	330	PW	130	330	1:1 PW	35	53 ±2µm	54 ±3µm	38	24	12.9	13.2
α_series	L-	124	-027/	315	PW	124	315	1:1 PW	27	40 ±2µm	41 ±3µm	54	45	17.9	18.4
α_series	L-	124	-030/	315	PW	124	315	1:1 PW	30	45 ±2µm	46 ±3µm	49	37	16.6	17.0
α_series	L-	120	-030/	305	PW	120	305	1:1 PW	30	46 ±2µm	46 ±3µm	53	41	18.6	18.6
α_series	UX	120	-033/	305	PW	120	305	1:1 PW	33	50 ±2µm	51 ±3µm	47	32	15.9	16.2
α_series	UX	120	-035/	305	PW	120	305	1:1 PW	35	53 ±2µm	54 ±3µm	45	29	15.5	15.8
α_series	UX	120	-040/	305	PW	118	300	1:1 PW	40	62 ±2µm	63 ±3µm	37	19	11.8	12.0
α_series	UX	110	-035/	280	PW	110	280	1:1 PW	35	53 ±2µm	54 ±3µm	53	34	18.1	18.4
α_series	UX	106	-040/	270	PW	106	270	1:1 PW	40	60 ±2µm	61 ±3µm	49	27	16.3	16.6
α_series	UX	100	-035/	255	PW	100	255	1:1 PW	35	53 ±2µm	54 ±3µm	64	41	21.9	22.3
α_series	UX	100	-040/	255	PW	100	255	1:1 PW	40	60 ±2µm	61 ±3µm	56	32	19.0	19.3
*)	EX	100	-048/	255	PW	100	255	1:1 PW	48	76 ±2µm	76 ±3µm	45	20	15.5	15.5
α_series	UX	90	-040/	230	PW	90	230	1:1 PW	40	60 ±2µm	61 ±3µm	67	37	22.1	22.5
α_series	UX	90	-045/	230	PW	90	230	1:1 PW	45	68 ±2µm	69 ±3µm	60	30	20.1	20.4
*)	EX	90	-048/	230	PW	88	225	1:1 PW	48	75 ±2µm	79 ±4µm	58	26	19.8	20.9
*)	EX	90	-055/	230	TW	88	225	2:1 TW	55	91 ±4µm	95 ±5µm	54	23	20.8	21.7
*)	EX	90	-071/	230	TW	88	225	3:1 TW	71	139 ±10µm	N/A	38	11	15.7	N/A
α_series	UX	90	-33x2	230	PW	90	230	1:1 PW	33	57 ±3µm	N/A	40	13	7.5	N/A
α_series	UX	79	-045/	200	PW	79	200	1:1 PW	45	68 ±2µm	69 ±3µm	81	41	27.7	28.1
*)	EX	79	-048/	200	PW	79	200	1:1 PW	48	75 ±2µm	79 ±4µm	75	35	26.2	27.6
*)	EX	79	-055/	200	PW	79	200	1:1 PW	55	88 ±4µm	88 ±4µm	69	30	26.0	26.0
α_series	UX	71	-045/	180	PW	71	180	1:1 PW	45	70 ±2µm	72 ±3µm	95	45	31.7	32.6
*)	EX	71	-048/	180	PW	71	180	1:1 PW	48	76 ±2µm	80 ±4µm	91	42	31.6	33.3

The above specification may be changed for quality improvement without notice.
* _EX SCREEN upgrade is also possible upon request.
Please ask your sales rep or supplier for availability and more information

High modulus polyester monofilament mesh
for high quality screen printing applications



Thread type

L : Conjugated Polyester Monofilament (27µmφ - 30 µmφ)
UX: Super High Modulus Polyester Monofilament (33µmφ - 45 µmφ)
EX: High Modulus Polyester Monofilament

NBC Meshtec inc.

Category	Mesh code				Mesh Count		Weaving	Thread diameter µm	Mesh thickness		Mesh opening µm	Open Area %	Theoretical ink volume	
	Thread type	Mesh/cm	Thread dia. Mesh/inch	Weaving	Tolerance ±3%				115-155cm µm	165cm & wider µm			115-155cm cm ³ /m ²	165cm & wider cm ³ /m ²
					/cm	/inch								
*)	EX	71 -055/	180	PW	71	180	1:1 PW	55	88 ±4µm	88 ±4µm	85	36	31.9	31.9
*)	EX	71 -063/	180	PW	71	180	1:1 PW	63	98 ±5µm	N/A	71	25	24.8	N/A
*)	EX	63 -048/	160	PW	63	160	1:1 PW	48	80 ±4µm	80 ±4µm	110	48	38.4	38.4
*)	EX	63 -063/	160	PW	63	160	1:1 PW	63	105 ±5µm	105 ±5µm	93	34	36.0	36.0
*)	EX	63 -071/	160	PW	63	160	1:1 PW	71	116 ±6µm	116 ±6µm	79	25	28.7	28.7
α_series	UX	59 -045/	150	PW	59	150	1:1 PW	45	72 ±2µm	74 ±4µm	124	54	38.6	39.7
*)	EX	59 -048/	150	PW	59	150	1:1 PW	48	76 ±2µm	80 ±4µm	120	50	38.2	40.2
*)	EX	59 -055/	150	PW	59	150	1:1 PW	55	88 ±4µm	88 ±4µm	114	45	39.9	39.9
*)	EX	59 -063/	150	PW	59	150	1:1 PW	63	105 ±5µm	105 ±5µm	104	38	39.9	39.9
*)	EX	59 -071/	150	PW	59	150	1:1 PW	71	116 ±6µm	116 ±6µm	91	29	33.5	33.5
*)	EX	55 -063/	140	PW	55	140	1:1 PW	63	105 ±5µm	105 ±5µm	116	41	43.2	43.2
*)	EX	55 -080/	140	PW	55	140	1:1 PW	80	140 ±7µm	140 ±7µm	97	29	40.0	40.0
α_series	UX	53 -045/	135	PW	53	135	1:1 PW	45	73 ±4µm	74 ±4µm	143	58	42.2	42.7
*)	EX	53 -048/	135	PW	53	135	1:1 PW	48	79 ±4µm	79 ±4µm	139	55	43.1	43.1
*)	EX	53 -055/	135	PW	53	135	1:1 PW	55	95 ±5µm	95 ±5µm	133	50	47.5	47.5
*)	EX	49 -071/	125	PW	49	125	1:1 PW	71	116 ±6µm	116 ±6µm	130	41	47.6	47.6
α_series	UX	47 -045/	120	PW	47	120	1:1 PW	45	73 ±4µm	74 ±4µm	167	62	45.4	46.1
*)	EX	47 -048/	120	PW	47	120	1:1 PW	48	80 ±4µm	80 ±4µm	163	59	47.4	47.4
*)	EX	47 -055/	120	PW	47	120	1:1 PW	55	95 ±5µm	95 ±5µm	157	55	52.3	52.3
*)	EX	47 -063/	120	PW	47	120	1:1 PW	63	105 ±5µm	105 ±5µm	149	50	52.0	52.0
*)	EX	47 -080/	120	PW	47	120	1:1 PW	80	137 ±7µm	137 ±7µm	130	38	51.4	51.4
*)	EX	43 -080/	110	PW	43	110	1:1 PW	80	132 ±7µm	132 ±7µm	150	42	55.7	55.7
*)	EX	39 -055/	100	PW	39	100	1:1 PW	55	95 ±5µm	95 ±5µm	199	61	58.3	58.3
*)	EX	39 -071/	100	PW	39	100	1:1 PW	71	122 ±6µm	122 ±6µm	182	51	62.6	62.6
*)	EX	39 -080/	100	PW	39	100	1:1 PW	80	134 ±7µm	134 ±7µm	174	47	62.9	62.9
*)	EX	35 -071/	90	PW	35	90	1:1 PW	71	125 ±6µm	125 ±6µm	210	55	69.2	69.2
*)	EX	35 -080/	90	PW	35	90	1:1 PW	80	137 ±7µm	137 ±7µm	202	51	70.2	70.2
*)	EX	31 -055/	80	PW	31	80	1:1 PW	55	95 ±5µm	95 ±5µm	263	69	65.2	65.2
*)	EX	31 -071/	80	PW	31	80	1:1 PW	71	125 ±6µm	125 ±6µm	246	60	75.0	75.0
*)	EX	31 -100/	80	PW	31	80	1:1 PW	100	170 ±9µm	170 ±9µm	218	47	80.1	80.1
*)	EX	27 -055/	70	PW	27	70	1:1 PW	55	95 ±5µm	95 ±5µm	308	72	68.4	68.4
*)	EX	27 -071/	70	PW	27	70	1:1 PW	71	125 ±6µm	125 ±6µm	291	64	80.4	80.4
*)	EX	27 -125/	70	PW	27	70	1:1 PW	125	240 ±24µm	240 ±24µm	238	43	103.3	103.3
*)	EX	24 -125/	60	PW	24	60	1:1 PW	125	230 ±23µm	230 ±23µm	298	50	114.0	114.0
*)	EX	24 -150/	60	PW	24	60	1:1 PW	150	260 ±26µm	260 ±26µm	271	41	106.5	106.5
*)	EX	20 -200/	50	PW	20	50	1:1 PW	200	370 ±37µm	370 ±37µm	308	37	136.0	136.0
*)	EX	16 -200/	40	PW	16	40	1:1 PW	200	370 ±37µm	370 ±37µm	435	47	173.6	173.6
*)	EX	12 -150/	30	PW	12	30	1:1 PW	150	290 ±29µm	290 ±29µm	696	68	196.0	196.0
*)	EX	12 -250/	30	PW	12	30	1:1 PW	250	480 ±48µm	480 ±48µm	597	50	238.7	238.7
*)	EX	10 -300/	25	PW	10	25	1:1 PW	300	600 ±60µm	600 ±60µm	547	29	173.9	173.9

The above specification may be changed for quality improvement without notice.

* _EX SCREEN upgrade is also possible upon request.

Please ask your sales rep or supplier for availability and more information